

Article Number: 184-11000



Slotted Cable and Wiring Duct, High-Density, 1" x 1", Non-Adhesive, PVC, Gray, 30 ft/boxDescription:

Base Data		
	Local Order Number	184-11000
	Туре	SLHD1X1
	Color	Gray (GY)
	Features and Benefits	 Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance. Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation. Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.
	Quantity Per	box
	Product Description	Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.
	Technical Description	Non-Adhesive
	Short Description	Slotted Cable and Wiring Duct, High-Density, 1" x 1", Non-Adhesive, PVC, Gray, 30ft/box
Product Dimensions		
	Length L (Imperial)	6.0ft
	Length L (Metric)	1.83m
	Width W (Imperial)	1.0"
	Width W (Metric)	25.4mm
	Width W2 (Imperial)	1.0"
	Width W2 (Metric)	25.4mm
	Width W3 (Imperial)	0.16"
	Width W3 (Metric)	4.1mm
	Width W4 (imperial)	0.4"
	Width W4 (metric)	10.2mm
	Width W5 (imperial)	0.75"
	Width W5 (metric)	19.05mm

4/28/2017 generated on:

184-11000



Product Dimensions Height H (Imperial) 1.06" Height H (Metric) 26.9mm Mounting Hole Centers (Imperial) 2.0"	
Height H (Metric) 26.9mm	
Mounting Hole Centers (Imperial) 2.0"	
Material and Specifications	
Material Polyvinylchloride (PVC)	
Material Shortcut PVC	
Flammability self-extinguishing	
Operating Temperature +122°F (+50°C)	
ROHS Compliant Yes	
Certification/Specification UL	
UL Recognized (US)	
Logistic and Packaging	
Package Quantity (Imperial) 30.0ft	
Package Quantity (Metric) 9.1m	
Customs Number(Schedule B) 3925900000	

generated on: 4/28/2017